



Cod.	Ø	Pz/Pcs	ØF	ØD	sp	Portata
111.9	9	100	Ø9	Ø15	5,6	3000 N
111.10	10	100	Ø10	Ø17,5	6	4500 N
111.11	11	100	Ø11	Ø19	6,5	5000 N
111.12	12	100	Ø12	Ø20	6,5	8500 N
111.12,5	12,5	100	Ø12,5	Ø20	7	3000 N
111.13	13	100	Ø13	Ø21	6,5	6000 N
111.14	14	100	Ø14	Ø22	6,7	9000 N
111.20	20	100	Ø20	Ø29	6,5	10000 N



Hinges doors and windows



Galvanized steel components



For a longer life it is recommended to load the bearing to 75% of its capacity. The specific regulations, depending on the different intended uses, must be considered in the design phase of the door / window.



Lubricate all parts in contact with grease (max. every 6 months) .
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.